



Flex wing design allows the machine to follow the ground contours.



FLEX WING GRASS TOPPER

The MAJOR Flex Wing Topper is a three point linkage mounted machine which folds up to give a 7'6" transport width.

Like all MAJOR machines, the Flex Wing topper is of robust construction. CE conformity is achieved through full PTO guarding and heavy rubber skirting to prevent debris from escaping.

The wing cutting decks are raised by hydraulic control to transport position. The wings are capable of flexing from -15 to +25 degrees allowing the cutting unit to follow the ground contours.

Contra-rotating swinging blades are retained in hardened steel bushing and clamped by springsteel blade backs. Undersole discs are fitted to prevent scalping and ensure a perfect finish every time.

FEATURES:

- Robust pivot points.
- Rubber shock absorbers
- Slip clutch PTO protection
- Patented transmission system
- Hydraulic wing lift
- ProCut swinging blades
- 88mm (3 1/2") blade overlap to eliminate striping

Model	Overall Width	Working Width	Transport Width	No. of Blades	No. of Rotors	Power (HP)	PTO rpm	Blade Speed	Cutting Height	Weight
12000FW-HD	3.8m (12' 4")	3.56m (12')	2.2m (7' 2")	16	4	50 - 160	540	74m/s	12-250mm	1116kg
18000FW-HD	5.6m (18' 4")	5.38m (18')	2.2m (7' 2")	24	6	60 - 160	540	74m/s	12-250mm	1395kg