



# ECO-AGI SLURRY PUMP

The MAJOR Eco-Agi Slurry Pump is designed to reduce the workload of the farmer and contractor.

It includes features such as the quick attach system. This pump can be lifted and lowered from the tank without removing the PTO shaft.

The nozzle rotates easily and can be locked in any position with a spring loaded pin. There is an adjustable hydraulic ram to suit individual tractors. The grid and removable rear walkway ensure operator safety. The tractor is protected from damage with a shearbolt in the PTO shaft.

## FEATURES:

- Quick attach lower linkage
- 310 degrees of horizontal adjustment with spring loaded lock
- Screw thread type adjuster to open and close nozzle c/w lock
- Marine bearing
- Chopper blade
- Fully galvanised body and frame
- Compact impeller head

Model	Drive	Working Depth	Power (HP)	PTO RPM	Weight (Kg)	Output (l/min)
AG7500	PTO	7'7"	90	540	595	13500



# MIX N' PUMP SLURRY AGITATOR PUMP

The MAJOR Mix 'n' Pump Agitator features an attachment mechanism which cuts the attachment time by half.

Operation of the pump is user friendly due to the cranked lower link bar and the hydraulic top link which sets the machine in the working position without having to detach and re-attach the PTO shaft.

The agitator impeller case is moulded to achieve the maximum pull on the material, most effective shearing action and greatest throw at the optimum speed without cavitation.

There are two models available – the AG6000 with a 6' working depth and the AG8000 with an 8' working depth.

## FEATURES:

- Three point linkage c/w hyd. top link
- Cat II lower link quick coupling
- Oil bath lubricated chain drive transmission
- Fully galvanised body
- Simple set up and operation from tractor cab

Model	Drive	Working Depth	Power (HP)	PTO RPM	Weight (Kg)	Output (l/min)
AG6000	Chain	6'	70	540	540	9240
AG8000	Chain	8'	70	540	560	9240