



# SIDE MOUNTED GRASS TOPPER

The MAJOR Side Mounted Topper is a fully offset three point linkage mounted pasture topper with two models offering 8' & 9' cutting widths.

This machine is robustly constructed with features including overlapping twin-cut high lift swinging blades with undersole discs.

Other features include hydraulic offset with an integrated hydraulic breakaway protecting the tractor from impact damage. The floating top link ensures the cutting deck hugs the ground contours with the damper bar removing any lateral vibration.



Hydraulic breakaway system

Undersole discs & swing blades

Tractor PTO protection is provided through the shearbolt & overrun.

## FEATURES:

- Heavy duty transmission
- Rubber shock absorbers between rotor gearboxes.
- Full hydraulic offset control
- Hydraulic breakaway system
- High lift twin-cut ProCut swinging blades

Model	Overall Width (incl. linkage in working position)	Working Width	Transport Width	No. of Blades	No. of Rotors	Power (HP)	PTO rpm	Blade Speed	Cutting Height	Weight
800SM	4.4m (14' 4")	2.4m (8')	2.22m (7' 3")	8	2	26-60	540	100m/s	12-250mm	550kg
900SM	4.5m (14' 7")	2.7m (9')	2.22m (7' 3")	8	2	37-67	540	111m/s	12-250mm	640kg