



9FTGD in transport position

Grass Toppers

TRAILED GRASS TOPPERS

The MAJOR Trailed Topper is a fully offset gear driven machine. It is offset for working and is folded into transport position hydraulically from the tractor seat.

This topper is available in 8', 9' and 12' cutting widths. The rotors are timed with each other and have an overlap of 3 inches (75mm). The blades rotate in opposite directions to each other and spreads the cut grass evenly behind the machine.

As the machine is fully offset there is no trampling of the pasture prior to cutting. The cutting height is set at the desired level

by moving the adjustable side skids to the appropriate position. There is a limit stop on the ram which controls the rear axle. When the operator reaches the field, the machine is offset then lowered and topping can commence. This reduces downtime.

FEATURES:

- Heavy duty transmission
- Rubber shock absorbers between rotor gearboxes
- Full hydraulic offset control
- Hydraulic breakaway system
- High lift twin-cut ProCut swinging blades
- Wide angle PTO shaft

Model	Overall Width (hitch eye to outer side)	Working Width	Transport Width	No. of Blades	No. of Rotors	Power (HP)	PTO rpm	Blade Speed	Cutting Height	Weight
8FTGD-HD	3.73m (12' 1")	2.4m (8')	2.6m (8' 5")	8	2	35 - 140	540	70m/s	12-205mm	550kg
9FTGD-HD	4.14m (13' 5")	2.7m (9')	2.9m (9' 5")	8	2	40 - 140	540	78m/s	12-205mm	650kg
12FTGDW-HD	4.62m (15')	3.57m (12')	2.6m (8' 5")	12	3	40 - 160	540	70m/s	12-205mm	1240kg